

Safety Data Sheet

resolve fifty one

01

Chemical Product and Company Identification Product Name Fifty One

Product Use Machine Dish Detergent

Product Code 3034

For Medical Emergency Call 'Chemtrec' 1-800-424-9300

Supplier's Information Santec Inc.

1420 East Linden Avenue, Linden NJ 07036

02

Hazards Identification GHS Classification:

1. Skin - Category 1

GHS Label Element:

Signal Word: Danger

2. Eyes - Category 1

Hazard Statement: Causes severe skin burns and eye damage.

Precautionary Statements: Wear protective gloves, splash goggles,

face shield, full suit, vapor respirator and boots.

Do not breathe mist/vapors/spray. Wash thoroughly after handling.



Eyes: Severely corrosive to the eyes. Causes severe burns. Eye exposure may cause severe and permanent eye injury (blindness).

Skin: Severely corrosive to the skin. Causes severe burns. The amount of tissue damage depends on length of contact. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

Inhalation: May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Inhalation of the spray or mist may produce severe irritation of respiratory tract, characterized by coughing, choking or shortness of breath.

Ingestion: Toxic if swallowed. May cause burns to mouth, throat and stomach. May be fatal is swallowed.

Chronic Effects

Carcinogenicity: No known critical effects or critical hazards.

Product /Ingredient Name: Not available.

03

Composition/ Information on Ingredients

| Name of Hazardous Ingredients | CAS No. | WT.% |
|-------------------------------|------------|-------|
| Potassium Hydroxide | 1310-58-3 | 10-20 |
| Sodium Hydroxide | 1310-73-2 | 5-10 |
| Potassium Silicate | 1312-76-1 | 1-5 |
| Polyacrylic Acid, Sodium Salt | 68479-09-4 | 1-5 |

04

First Aid Measures **Eye Contact:** Check for and remove any contact lenses. Flush with large quantities of water, holding eyelids open for 15 minutes. Seek medical attention immediately.

Skin Contact: Wash skin with copious amounts of water. Seek medical attention immediately.

Inhalation: Remove to fresh air. Seek medical attention immediately.

Ingestion: Do not induce vomiting. Drink copious amounts of water. Seek medical attention immediately.

05

Fire Fighting Measures

Suitable Fire Extinguishing Media: Use water spray, fog or foam

Specific Hazards Arising from the Chemical: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous Thermal Decomposition Products: Decomposition products may include following materials; Carbon Dioxides, Carbon Monoxides, Sulfur Dioxides.

Specific Fire-Fighting Methods: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. **Specific Protective Equipment for Fire-Fighters:** Fire-Fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

06

Accidental Release Measures **Spill Clean Up:** Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move Containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Page: 1 of 3



Safety Data Sheet

resolve fifty one

Handling and Storage

Handling: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Wash thoroughly after handling.

Page: 2 of 3

Storage: Store between the following temperatures: 4.44 to 48.9°C (40 to 120°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

Exposure Controls/ Personal Protection **Ingredient Name Exposure Limits** OSHA PEL 2 mg/m³ Sodium Hydroxide OSHA PEL 2 mg/m³

Personal Protective Equipment (PPE)

Eyes: Splash goggles or face shield.

Potassium Hydroxide

Skin: Use synthetic apron, other protective equipment as necessary to prevent skin contact.

Body: Face shield, full suit, vapor respirator, boots and gloves.

Respiratory: A self contained breathing apparatus should be used to avoid inhalation of product. Be sure to use

an approved /certified respirator or equivalent.

Physical and Chemical **Properties**

Physical State Clear liquid Color Tan Odor Bland рΗ > 13 Flash point None **Explosion limits** Not available

Not available Flammability (solid, gas) Not available **Melting point** >100°C (212F) **Boiling point** Evaporation rate (butyl acetate = 1) Not available Vapor pressure Not available Vapor density Not available Relative density 1.20 (Water = 1)

Solubility Easily soluble in the following materials: cold water and hot water

Partition coefficient n-octano/water Not available Not available **Auto-ignition temperature Decomposition temperature** Not available **Odor threshold** Not available

Viscosity Kinematic (room temperature): < 10 cSt (CPS)

Stability and Reactivity

Stability: The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid: Strong acids.

Materials to avoid: Reactive with oxidizing agents, reducing agents, metals, acids.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition should not be produced. If heated, see section 05.



Safety Data Sheet resolve fifty one

Date of Issue: 05/30/2018

Page: 3 of 3

| 11 | Toxicological Information | Product /Ingredient Name Potassium Hydroxide Sodium Hydroxide Potassium Silicate Polyacrylic Acid, Sodium Salt | LD: LD: LD: | sult 50 Oral 50 Oral 50 Oral 50 Oral | Species Rat Rat Rat Rat | Dose 500-1000 mg/kg 500 mg/kg 1500-3200 mg >5000 mg/kg | | | |
|----|------------------------------|---|--|--|---|---|---|-------------|--|
| 12 | Ecological Information | N/A | | | | | | | |
| 13 | Disposal Considerations | Waste Information Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information. | | | | | | | |
| 14 | Transport Information | Regulatory Information | UN Number | Proper S | Shipping Nam | e Classes | PG* | Label | |
| | | DOT Classification | UN3266 | inorganic, | | 8 odium hydroxide | | | |
| | | Note: DOT classification applies to most package sizes. For specific container size classifications or size exceptions, refer to the bill of lading with your shipment. PG*: Packing Group | | | | | | | |
| 15 | Regulatory Information | U.S. Federal Regulations TSCA 8(b) inventory: All components are listed or exempted. SARA 302/304/311/312 extremely hazardous substances: No listed substance SARA 302/304 emergency planning and notification: No listed substance | | | | | | | |
| | | SARA 313 Form R-Reporting requirements | Product na No listed sub | | CAS number | Con | <u>centrati</u> | <u>on</u> | |
| 16 | Other Information | To the best of our knowledge, the the above named supplier nor an accuracy of completeness of the Final determination of suitabilit materials may present unknown hazards are described herein, we | ny of its subsidiarie information contai ty of any material I hazards and shoul | s assumes any ned herein. is the sole re d be used wi | y liability whats esponsibility of th caution. Alth | the user. All nough certain | *Hazard System Health Reactiv Flamm | 3 vity 0 | |

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimum hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.