

## Safety Data Sheet

#### resolve five

Page: 1 of 3

01

Chemical Product and Company Identification Product Name Five

Product Use Oven and Grill Cleaner

Product Code 3508

For Medical Emergency Call 'Chemtrec' 1-800-424-9300

**Supplier's Information** Santec Inc.

1420 East Linden Avenue, Linden NJ 07036

02

Hazards Identification GHS Classification: 1. Skin - Category 1

**GHS Label Element:** 

2. Eyes - Category 1

Signal Word: Danger

**Hazard Statement:** Causes severe skin burns and eye damage. **Precautionary Statements:** Wear protective gloves, splash goggles,

face shield, full suit, vapor respirator and boots. Do not breathe

mist /vapors /spray. Wash thoroughly after handling.

**Acute Effects** 

**Eyes:** Severely corrosive to the eyes. Causes severe burns. Eye exposure may cause severe and permanent eye injury (blindness).

**Skin:** Severely corrosive to the skin. Causes severe burns. The amount of tissue damage depends on length of contact. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

**Inhalation:** May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Inhalation of the spray or mist may produce severe irritation of respiratory tract, characterized by coughing, choking or shortness of breath.

Ingestion: Toxic if swallowed. May cause burns to mouth, throat and stomach. May be fatal is swallowed.

**Chronic Effects** 

Carcinogenicity: No known critical effects or critical hazards.

Product /Ingredient Name: Not available.

03

Composition/ Information on Ingredients

Name of Hazardous Ingredients	CAS No.	WT.%
Sodium Hydroxide	1310-73-2	8-10
Diethylene Glycol Monobutyl Ether	112-34-5	4-6
Sodium Xylene Sulfonate	1300-72-7	4-6
Nonylphenol Ethoxylate	127087-87-0	1-3

04

First Aid Measures **Eye Contact:** Check for and remove any contact lenses. Flush with large quantities of water, holding eyelids open for 15 minutes. Seek medical attention immediately.

Skin Contact: Wash skin with copious amounts of water. Seek medical attention immediately.

Inhalation: Remove to fresh air. Seek medical attention immediately.

Ingestion: Do not induce vomiting. Drink copious amounts of water. Seek medical attention immediately.

05

Fire Fighting Measures Suitable Fire Extinguishing Media: Use water spray, fog or foam

**Specific Hazards Arising from the Chemical:** In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous Thermal Decomposition Products:** Decomposition products may include following materials; Carbon Dioxides, Carbon Monoxides, Sulfur Dioxides.

**Specific Fire-Fighting Methods:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. **Specific Protective Equipment for Fire-Fighters:** Fire-Fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

06

Accidental Release Measures **Spill Clean Up:** Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move Containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

santec, inc. 1420 East Linden Ave, Linden NJ 07036 T 908-912-2500 F 908-374-7149 info@cleanneeds.com



## Safety Data Sheet

### resolve five

Page: 2 of 3

07

Handling and Storage

**Handling:** Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Wash thoroughly after handling.

**Storage:** Store between the following temperatures: 4.44 to 48.9°C (40 to 120°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

80

Exposure Controls/ Personal Protection Ingredient Name

Exposure Limits
OSHA PEL 2 mg/m<sup>3</sup>

Sodium Hydroxide Diethylene Glycol Monobutyl Ether

OSHA TWA 35 ppm

#### **Personal Protective Equipment (PPE)**

Eyes: Splash goggles or face shield.

Skin: Use synthetic apron, other protective equipment as necessary to prevent skin contact.

**Body:** Face shield, full suit, vapor respirator, boots and gloves.

Respiratory: A self contained breathing apparatus should be used to avoid inhalation of product. Be sure to use

an approved /certified respirator or equivalent.

09

Physical and Chemical Properties

Physical StateClear liquidColorDull RedOdorSlight Organic

**pH** ≥ 13

Flash point >74°C (165°F) **Explosion limits** Not available Flammability (solid, gas) Not available **Melting point** Not available >100°C (212F) **Boiling point** Evaporation rate (butyl acetate = 1) Not available Vapor pressure Not available Vapor density Not available Relative density 1.10 (Water = 1)

**Solubility** Easily soluble in the following materials: cold water and hot water

Partition coefficient n-octano/water
Auto-ignition temperature
Decomposition temperature
Odor threshold
Not available
Not available
Not available

Viscosity Kinematic (room temperature): ≤ 10 cSt (CPS)

10

Stability and Reactivity

**Stability:** The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid: Strong acids.

Materials to avoid: Reactive with oxidizing agents, reducing agents, metals, acids.

**Hazardous decomposition products:** Under normal conditions of storage and use, hazardous decomposition should not be produced. If heated, see section 05.



# Safety Data Sheet resolve five

Date of Issue: 05/30/2018

Page: 3 of 3

11	Toxicological Information	Product /Ingredient Name Sodium Hydroxide Diethylene Glycol Monobutyl Ethe Sodium Xylene Sulfonate Nonylphenol Ethoxylate	Result LD50 Oral er LD50 Oral LD50 Oral LD50 Oral	Species Rat Rat Rat Rat	<b>Dose</b> 500 mg/kg 5660 mg/kg 2500 mg/kg 960 - 3980	1		
12	Ecological Information	N/A						
13	Disposal Considerations	Waste Information Waste must be disposed of in a Consult your local or regional au				nmental cor	itrol regu	lations.
14	Transport Information	Regulatory Information  DOT Classification	<b>UN Number</b> UN3266	Proper Ship Corrosive liquinorganic, n.o. (sodium hydro	uid, basic, .s.	Classes 8	PG*	Label
		<b>Note:</b> DOT classification applies exceptions, refer to the bill of ladi <b>PG*:</b> Packing Group			container size o	classification	s or size	
15	Regulatory Information	U.S. Federal Regulations TSCA 8(b) inventory: All comp SARA 302/304/311/312 extre SARA 302/304 emergency pl	emely hazardous	substances: Nication: No liste	ed substance			
		SARA 313 Form R-Reporting requirements	Product nar No listed subs		<u>S number</u>	Cor	centrati	<u>on</u>
16	Other Information	To the best of our knowledge, neither the above named supplie er for the accuracy of completene Final determination of suitability materials may present unknown h hazards are described herein, we	r nor any of its subs ess of the information of any material is nazards and should	idiaries assumes on contained her the sole respon be used with cau	any liability whein. sibility of the ation. Although	natsoev- user. All n certain	*Hazard System ( Health Reactiv Flamma	3 vity 0

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimum hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.