

Safety Data Sheet

resolve twenty four

Chemical Product and Company Identification **Product Name** Twenty Four

Product Use Heavy Duty Clinging Oven Cleaner

Product Code 3870

For Medical Emergency Call 'Chemtrec' 1-800-424-9300

Supplier's Information Santec Inc.

1420 East Linden Avenue, Linden NJ 07036

GHS Label Element:

Hazards Identification **GHS Classification:** 1. Skin - Category 1

2. Eyes - Category 1

Signal Word: Danger

Hazard Statement: Causes severe skin burns and eye damage.

Precautionary Statements: Wear protective gloves, splash goggles,

face shield, full suit, vapor respirator and boots.

Do not breathe mist /vapors /spray. Wash thoroughly after handling.

Acute Effects

Eyes: Severely corrosive to the eyes. Causes severe burns. Eye exposure may cause severe and permanent eye injury (blindness).

Skin: Severely corrosive to the skin. Causes severe burns. The amount of tissue damage depends on length of contact. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

Inhalation: May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Inhalation of the spray or mist may produce severe irritation of respiratory tract, characterized by coughing, choking or shortness of breath.

Ingestion: Toxic if swallowed. May cause burns to mouth, throat and stomach. May be fatal is swallowed.

Chronic Effects

Carcinogenicity: No known critical effects or critical hazards.

Product /Ingredient Name: Not available.

Information on **Ingredients**

Name of Hazardous Ingredients	CAS No.	WT.%
Sodium Hydroxide	1310-73-2	5-8
Nonylphenol Ethoxylate	127087-87-0	0-2
Tall Oil Fatty Acid	61790-12-3	0-2
Disodium Cocoampho Dipropionate	68604-71-7	0-2

First Aid Measures Eye Contact: Check for and remove any contact lenses. Flush with large quantities of water, holding eyelids open for 15 minutes. Seek medical attention immediately.

Skin Contact: Wash skin with copious amounts of water. Seek medical attention immediately.

Inhalation: Remove to fresh air. Seek medical attention immediately.

Ingestion: Do not induce vomiting. Drink copious amounts of water. Seek medical attention immediately.

Fire Fighting Measures

Suitable Fire Extinguishing Media: Use water spray, fog or foam

Specific Hazards Arising from the Chemical: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous Thermal Decomposition Products: Decomposition products may include following materials; Carbon Dioxides, Carbon Monoxides.

Specific Fire-Fighting Methods: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Specific Protective Equipment for Fire-Fighters: Fire-Fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

()6

Accidental Release Measures

Spill Clean Up: Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move Containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Page: 1 of 3



Safety Data Sheet

resolve twenty four

Page: 2 of 3

07

Handling and Storage

Handling: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Wash thoroughly after handling.

Storage: Store between the following temperatures: 4.44 to 48.9°C (40 to 120°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

80

Exposure Controls/ Personal Protection Ingredient Name Sodium Hydroxide Exposure Limits
OSHA PEL 2 mg/m³

Personal Protective Equipment (PPE)

Eyes: Splash goggles or face shield.

Skin: Use synthetic apron, other protective equipment as necessary to prevent skin contact.

Body: Face shield, full suit, vapor respirator, boots and gloves.

Respiratory: A self contained breathing apparatus should be used to avoid inhalation of product. Be sure to use

an approved /certified respirator or equivalent.

09

Physical and Chemical Properties

Physical StateClear viscous liquidColorGolden Yellow

OdorBlandpH≥ 13Flash pointNoneExplosion limitsNot available

Flammability (solid, gas)

Melting point

Boiling point

Evaporation rate (butyl acetate = 1)

Vapor pressure

Vapor density

Relative density

Not available

Not available

Not available

Not available

1.08 (Water = 1)

Solubility Easily soluble in the following materials: cold water and hot water

Partition coefficient n-octano/water
Auto-ignition temperature
Decomposition temperature
Odor threshold
Not available
Not available
Not available

Viscosity Kinematic (room temperature): 250-300 cSt (CPS)

10

Stability and Reactivity

Stability: The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid: Strong acids.

Materials to avoid: Reactive with oxidizing agents, reducing agents, metals, acids.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition should not be produced. If heated, see section 05.



Safety Data Sheet resolve twenty four

Page: 3 of 3

11	Toxicological Information	Product /Ingredient Name Sodium Hydroxide Nonylphenol Ethoxylate Tall Oil Fatty Acid Disodium Cocoampho Dipropionat	Result LD50 Oral LD50 Oral LD50 Oral e N/A	Species Rat Rat Rat N/A	Dose 500 mg/kg 960 - 3980 >10,000 mg N/A					
12	Ecological Information	N/A								
13	Disposal Considerations	Waste Information Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.								
14	Transport Information		JN Number JN3266	Proper Ship Corrosive liquinorganic, n.o (sodium hydro	id, basic, .s.	Classes	PG*	Label		
		Note: DOT classification applies to most package sizes. For specific container size classifications or size exceptions, refer to the bill of lading with your shipment. PG*: Packing Group								
15	Regulatory Information U.S. Federal Regulations TSCA 8(b) inventory: All components are listed or exempted. SARA 302/304/311/312 extremely hazardous substances: No listed substance SARA 302/304 emergency planning and notification: No listed substance									
		SARA 313 Form R-Reporting requirements	Product name No listed substa		number	Co	ncentrati	<u>on</u>		
16	Other Information	To the best of our knowledge, the neither the above named supplier in er for the accuracy of completeness. Final determination of suitability of materials may present unknown has hazards are described herein, we exist.	or any of its subsidi of the information of any material is th zards and should be	iaries assumes a contained here ne sole respons e used with cau	any liability whe in. ibility of the ution. Although	atsoev- user. All certain	*Hazard C System (H Health Reactivit	3 0		

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimum hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.

Date of Issue: 05/31/2018